

Portable Mancooler® - 115V

Belt Drive Models



2 Year Warranty - Engineered for Superior Performance

FEATURES ON ALL BELT DRIVE MANCOOLERS®

Guards & Barrel Are Epoxy Coated

MC42OS

- 115V, 1 Phase, 2 Speed, ODP, 1 HP Motor
- · Epoxy Coated Steel Spiral, Vibration Isolated Mounted Guards
- 20 Gauge Roll Form, Epoxy Coated Housing
- · Steel Hubbed Wheels with Locking Casters
- Compliant with OSHA Requirements
- SJT 10' Cord with Three Prong Plug
- · Full Width Handle with Cord Wrap
- Four Bladed Aluminum Propeller
- Quiet Dba: High 75, Low 67
- · Motor Out of Air Stream
- · 2 Speed Rocker Switch
- Fully Assembled

| EDP No. | Catalog No. | Prop Dia. | Fan Style | НР | Cabinet Size | CFM | | RPM | | Ship Wt. |
|---------|-------------|-----------|-----------|----|--------------|-------|------|------|-----|----------|
| | | | | | | High | Low | High | Low | Ship Wt. |
| 60002 | MC42OS | 42" | Portable | 1 | 46" | 17100 | 9558 | 430 | 285 | 130 |



2 Year Warranty

EMC42D

- 115V, 1/2 HP, 2 Speed, 1 Phase, ODP, Ball Bearing Motor, Rocker Switch
- Epoxy Coated Steel Spiral, Resiliant Mounted Guards
- · 20 Gauge Roll Form Epoxy Coated Housing
- 10' Three Conductor SJT Type Cord
- Compliant with OSHA Requirements
- 45" Diameter Barrel with 15" Width
- Full Width Easy Grip Handle
- Aluminum 3 Blade PropFully Assembled
- 8" Steel Wheels

| EDP No. | Catalog No. | Prop Dia. | Fan Style | НР | Cabinet | CFM | | RPM | | Ship Wt. |
|---------|----------------------|-----------|-----------------------|-----|---------|-------|------|------|-----|----------|
| EDF NO. | | | | | Size | High | Low | High | Low | Ship wt. |
| 60007 | EMC42D | 42" | Portable | 1/2 | 46" | 14000 | 8000 | 540 | 400 | 120 |
| 05242 | Blade Ass'y - EMC42D | 42" | Replacement Propeller | | | | | | | 7 |



2 Year Warranty

MC42 / MC48 Swivel Mounts

- 115V, 1 Phase, 1 Speed, ODP, ³/₄ HP (42") & 1 PH (48") Motor
- · 12' Three Conductor SJT Type Cord and Switch
- Four Bladed Epoxy Coated Steel Propeller
- 4" Steel Wheels with Rubber Tires
- · Pull Handle with Cord Wrap
- Tiltable 30°, Locks in Place



| EDP No. | Catalog No. | Prop Dia. | HP | Cabinet Size | CFM | RPM | Ship Wt. |
|---------|-------------|-----------|---------------|--------------|-------|-----|----------|
| 60025 | MC42B | 42" | 3/4 (2 Speed) | 42½" | 16180 | 380 | 135 |
| 60026 | MC48B | 48" | 1 (1 Speed) | 48½" | 17730 | 385 | 160 |