

Ceiling Fans - High Volume Low Speed (HVLS)



HVLS

Continuous Duty

Features

HVLS

- 1 and 2 HP 230/460V with capability to move nearly to 275,000 CFM
- 30 Amp Disconnect switch
- Available in 3-Blade and 6-Blade configurations
- Range from 8 ft. to 24 ft. foot diameter
- Direct I-beam mount , 1 ft Pivot Extension Assembly, 2 ft. Mounting Extension
- Lifetime Warranty on Blades and Hub, limited 5 year warranty on the gear motor



HVLS Ceiling Fan - 3 Blade

EDP #	Fan Size In Diameter	Watts 230/460	HP	RPM	CFM		Noise Level	Weight
					Forward	Reverse		
40141	8'	550	1	168	28,200	8,000	57 dB	185 lbs.
40142	12'	746	1	116	47,000	25,000	59 dB	205 lbs.
40143	16'	710	1.5	79	78,000	32,000	59.8dB	250 lbs.
40144	20'	1490	2	73	142,500	54,500	60 dB	284 lbs.
40145	24'	1410	2	53	186,500	96,500	58.5 dB	302 lbs.

HVLS Ceiling Fan - 6 Blade

EDP#	Fan Size In Diameter	Watts 230/460	HP	RPM	CFM		Thrust		Noise Level	Weight
					Forward	Reverse	Forward	Reverse		
40146	8'	550	1	168	41,500	12,300	22 lb.	2 lb.	57 dB	240 lbs.
40147	12'	746	1	116	69,500	39,200	27 lb.	9 lb.	59 dB	280 lbs.
40148	16'	710	1.5	79	115,000	49,300	42 lb.	12 lb.	59.8dB	342 lbs.
40149	20'	1490	2	73	210,000	84,400	127 lb.	30 lb.	60 dB	398 lbs.
40151	24'	1410	2	53	275,000	149,000	105 lb.	47 lb.	58.5 dB	437 lbs.



Warning: Cancer and Reproductive Harm www.P65Warnings.ca.gov

This warning is applicable to all products on this page, see page i2 for more information